

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/007877 A1

- (51) International Patent Classification⁷: **E05B 13/00**, 13/10
- (21) International Application Number: PCT/GB2003/003003
- (22) International Filing Date: 11 July 2003 (11.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0216354.1 12 July 2002 (12.07.2002) GB
- (71) Applicant (for all designated States except US): **SUPERIOR INVESTMENTS LIMITED** [GB/GB]; Millfield House, Millfield Road, Ettingshall, Wolverhampton WV4 6JE (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HEELEY, Peter** [GB/GB]; Llety Dafydd, Meifod, Powys SY22 6HL (GB). **JONES, Phillip, David** [GB/GB]; 9 Porthill Gardens, Shrewsbury, Shropshire SY3 9SH (GB).
- (54) Title: **DOOR LOCKING MECHANISM**
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(57) **Abstract:** A locking mechanism (1) is provided for a door latch mechanism in which a latch spindle is turnable to withdraw a latch bolt of the latch mechanism from a latching position into which it is spring biased. The locking mechanism comprises a lever handle (5) having a fluted passageway (24) for fitting to an adjacent end of the latch spindle. The passageway enables the handle to turn relatively to the latch spindle in opposite directions through a predetermined angle of movement. At one end of this angle of movement, the handle is in a horizontal rest position and is engageable with the latch spindle for turning the spindle in a direction to withdraw the latch bolt from its latching position and, at the opposite end, the handle is in a lifted locking position and is engageable with the spindle to prohibit turning thereof in the opening direction. At the locking position, a locking member (27) slidably mounted in the handle and controlled by a trigger part (30), extending behind the lever part (8) of the handle is engageable in one of a pair of retainer holes (33,34) depending on the handing of the lever handle.